



DIESELMAR MR 4040

Features

Mono-grade lubricant made from a blend of highly refined base oils and chemical additives that confer detergent / dispersant properties in order to minimize the deposit build-up in the engine, as well as characteristics of anti-wear, antirust, anti-foaming and anti-corrosion, to ensure adequate crankcase and cylinder lubrication of medium speed diesel engines. Meets the applicable specifications at service level API CF.

OIL AMERICA, INC.



Usage

Specifically formulated for the lubrication of medium speed diesel engines using residual fuel with sulfur content greater than 2.5% by weight.

Specifications

Physicochemical Properties	Method ASTM	Units	3030	4020	4030	4040
Viscosity at 40°C	D 445	cST	103	130	135	135
Viscosity at 100°C	D 445	cST	11.5	14	14	14
Viscosity Index	D 2270		100	100	100	100
Pour Point	D 97	°C	-12	-12	-12	-12
Flashpoint	D 92	°C	230	230	230	240
Density at 15.6°C	D 1298	Kg/lit	0.895	0.905	0.898	0.897
Basic Number	D 2896	mg KOH/g	30	20	30	40



Distributed by:
OIL AMERICA, INC.

Calle 51 y Manuel María Icaza - Building Proconsa 1 - Floor No. 4 - Office #4A
Panama, Rep. of Panama - Tel.: (+507) 264-2399 - 264-2579 - 395-9578
Email: petroamerica@cwpanama.net - www.oilamerica.com.pa

Product produced complying standards ISO 9001/2002 and ISO/TS 16949 2002 by
Petroles de Venezuela, S.A.

